

5.47: CCgHelper::RetrieveCardInfo, CgEnterExclusiveMode: OK.  
5.47: Cg: CardGnome v1.0 (Unicode static library, loglevel=1)  
5.47: Cg: Loading resources from resource 0x400000 (EXE)  
5.47: Cg: Successfully loaded information for 59 cards  
5.47: Cg: Listener thread started  
5.47: Cg: New listener thread duty is 'Idle'  
5.140: Cg: Notification window initialized  
5.140: Cg: Checking actual state of the system at startup...  
5.140: Cg: Card state has been silently set to CardStateStopped  
5.172: Cg: No PCMCIA cards detected, rc=0xd  
5.187: Cg: Found USB device with hardware ID  
[USB\ROOT\_HUB&VID8086&PID7112&REV0000,USB\ROOT\_HUB&VID8086&PID7112,USB\ROOT\_HUB],  
checking it...  
5.187: Cg: Found USB device with hardware ID  
[USB\ROOT\_HUB20&VID15AD&PID0770&REV0000,USB\ROOT\_HUB20&VID15AD&PID0770,USB\ROOT  
\_HUB20], checking it...  
5.187: Cg: Found USB device with hardware ID  
[USB\Vid\_0af0&Pid\_6901&Rev\_0000,USB\Vid\_0af0&Pid\_6901], checking it...  
5.187: Cg: DevNode 0x874 status is 0x180600a, problem# is 0 (active)  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_1022&DEV\_2000&SUBSYS\_20001022&REV\_10,PCI\VEN\_1022&DEV\_2000&SUBSYS\_20001022,  
PCI\VEN\_1022&DEV\_2000&CC\_020000,PCI\VEN\_1022&DEV\_2000&CC\_0200], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_104B&DEV\_1040&SUBSYS\_1040104B&REV\_01,PCI\VEN\_104B&DEV\_1040&SUBSYS\_1040104  
B,PCI\VEN\_104B&DEV\_1040&CC\_010000,PCI\VEN\_104B&DEV\_1040&CC\_0100], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_1274&DEV\_1371&SUBSYS\_13711274&REV\_02,PCI\VEN\_1274&DEV\_1371&SUBSYS\_13711274,  
PCI\VEN\_1274&DEV\_1371&CC\_040100,PCI\VEN\_1274&DEV\_1371&CC\_0401], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_0405&SUBSYS\_040515AD&REV\_00,PCI\VEN\_15AD&DEV\_0405&SUBSYS\_040515  
AD,PCI\VEN\_15AD&DEV\_0405&CC\_030000,PCI\VEN\_15AD&DEV\_0405&CC\_0300], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_0740&SUBSYS\_074015AD&REV\_10,PCI\VEN\_15AD&DEV\_0740&SUBSYS\_074015  
AD,PCI\VEN\_15AD&DEV\_0740&CC\_088000,PCI\VEN\_15AD&DEV\_0740&CC\_0880], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_0770&SUBSYS\_077015AD&REV\_00,PCI\VEN\_15AD&DEV\_0770&SUBSYS\_077015  
AD,PCI\VEN\_15AD&DEV\_0770&CC\_0C0320,PCI\VEN\_15AD&DEV\_0770&CC\_0C03], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_0790&SUBSYS\_00000000&REV\_02,PCI\VEN\_15AD&DEV\_0790&SUBSYS\_0000000  
0,PCI\VEN\_15AD&DEV\_0790&REV\_02,PCI\VEN\_15AD&DEV\_0790,PCI\VEN\_15AD&DEV\_0790&CC\_0604  
01,PCI\VEN\_15AD&DEV\_0790&CC\_0604], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_00000000&REV\_01,PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_000000  
00,PCI\VEN\_15AD&DEV\_07A0&REV\_01,PCI\VEN\_15AD&DEV\_07A0,PCI\VEN\_15AD&DEV\_07A0&CC\_06  
0400,PCI\VEN\_15AD&DEV\_07A0&CC\_0604], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_00000000&REV\_01,PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_000000  
00,PCI\VEN\_15AD&DEV\_07A0&REV\_01,PCI\VEN\_15AD&DEV\_07A0,PCI\VEN\_15AD&DEV\_07A0&CC\_06  
0400,PCI\VEN\_15AD&DEV\_07A0&CC\_0604], checking it...  
5.234: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_00000000&REV\_01,PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_000000  
00,PCI\VEN\_15AD&DEV\_07A0&REV\_01,PCI\VEN\_15AD&DEV\_07A0,PCI\VEN\_15AD&DEV\_07A0&CC\_06  
0400,PCI\VEN\_15AD&DEV\_07A0&CC\_0604], checking it...  
5.250: Cg: Found PCI device with hardware ID  
[PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_00000000&REV\_01,PCI\VEN\_15AD&DEV\_07A0&SUBSYS\_000000  
00,PCI\VEN\_15AD&DEV\_07A0&REV\_01,PCI\VEN\_15AD&DEV\_07A0,PCI\VEN\_15AD&DEV\_07A0&CC\_06  
0400,PCI\VEN\_15AD&DEV\_07A0&CC\_0604], checking it...





PCI\VEN\_8086&DEV\_7110&REV\_08,PCI\VEN\_8086&DEV\_7110,PCI\VEN\_8086&DEV\_7110&CC\_060100,PCI\VEN\_8086&DEV\_7110&CC\_0601], checking it...

5.281: Cg: Found PCI device with hardware ID

[PCI\VEN\_8086&DEV\_7111&SUBSYS\_197615AD&REV\_01,PCI\VEN\_8086&DEV\_7111&SUBSYS\_197615AD,PCI\VEN\_8086&DEV\_7111&CC\_01018A,PCI\VEN\_8086&DEV\_7111&CC\_0101], checking it...

5.281: Cg: Found PCI device with hardware ID

[PCI\VEN\_8086&DEV\_7112&SUBSYS\_197615AD&REV\_00,PCI\VEN\_8086&DEV\_7112&SUBSYS\_197615AD,PCI\VEN\_8086&DEV\_7112&CC\_0C0300,PCI\VEN\_8086&DEV\_7112&CC\_0C03], checking it...

5.281: Cg: Found PCI device with hardware ID

[PCI\VEN\_8086&DEV\_7190&SUBSYS\_00000000&REV\_01,PCI\VEN\_8086&DEV\_7190&SUBSYS\_00000000,PCI\VEN\_8086&DEV\_7190&REV\_01,PCI\VEN\_8086&DEV\_7190,PCI\VEN\_8086&DEV\_7190&CC\_060000,PCI\VEN\_8086&DEV\_7190&CC\_0600], checking it...

5.281: Cg: Found PCI device with hardware ID

[PCI\VEN\_8086&DEV\_7191&SUBSYS\_00000000&REV\_01,PCI\VEN\_8086&DEV\_7191&SUBSYS\_00000000,PCI\VEN\_8086&DEV\_7191&REV\_01,PCI\VEN\_8086&DEV\_7191,PCI\VEN\_8086&DEV\_7191&CC\_060400,PCI\VEN\_8086&DEV\_7191&CC\_0604], checking it...

5.281: Cg: -----

5.281: Cg: Supported card Scorpion detected with hardware ID [USB\Vid\_0af0&Pid\_6901&Rev\_0000] & devnode 0x874

5.281: Cg: -----

5.281: Cg: Modem detection method is set to ModemDetMethodDefaultPolling

5.281: Cg: Application port detection method is set to AppPortDetMethodDefaultPolling

5.281: Cg: Application2 port detection method is set to AppPortDetMethodDefaultPolling

5.281: Cg: Debug port detection method is set to DbgPortDetMethodDefaultPolling

5.281: Cg: Card state changed to Starting

5.281: Cg: Detection timeout timer started with 300000 msec timeout

5.281: Cg: Polling timer started with 1 sec frequency

5.281: Cg: This card has NO modem device and has a WWAN NIC device

5.281: Cg: This card has a primary application port

5.281: Cg: This card has NO secondary application port

5.281: Cg: Searching for port [Application Interface] with parent 0x874

5.390: Cg: Checking port #0 [Puerto de impresora (LPT1)]

5.390: Cg: Checking port #1 [Puerto de comunicaciones (COM1)]

5.390: Cg: Checking port #2 [Puerto de comunicaciones (COM2)]

5.390: Cg: Checking port #3 [GlobeTrotter Module HSDPA Application Interface (COM4)]

5.390: Cg: DevNode 0x2010 status is 0x180600a, problem# is 0 (active)

5.390: Cg: Corresponding application port found on \\.\COM4 with devnode 0x2010

5.390: Cg: Final port could be opened successfully

5.390: Cg: This card has NO smart card reader device

5.390: Cg: Searching for network adapter [GlobeTrotter] with parent 0x874

5.500: Cg: Checking network adapter #0 [GlobeTrotter Module HSDPA Network Card]

5.500: Cg: DevNode 0x1f80 status is 0x180600a, problem# is 0 (active)

5.500: Cg: Corresponding WWAN network adapter GlobeTrotter Module HSDPA Network Card found with devnode 0x1f80 (NetCfgInstanceId={FE74B4D1-D277-4C2B-840A-EE455A352104})

5.500: Cg: Corresponding WWAN NDIS port found under \\.\GTNDIS0

5.500: Cg: Searching for port [Diagnostics Interface] with parent 0x874

5.609: Cg: Checking port #0 [Puerto de impresora (LPT1)]

5.609: Cg: Checking port #1 [Puerto de comunicaciones (COM1)]

5.609: Cg: Checking port #2 [Puerto de comunicaciones (COM2)]

5.609: Cg: Checking port #3 [GlobeTrotter Module HSDPA Application Interface (COM4)]

5.609: Cg: Checking port #4 [GlobeTrotter Module HSDPA Diagnostics Interface (COM3)]

5.609: Cg: DevNode 0x1fcc status is 0x180600a, problem# is 0 (active)

5.609: Cg: Corresponding debug port found on \\.\COM3 with devnode 0x1fcc

5.609: Cg: Bus device found (\\.\gtsbus0)

5.640: Cg: Driver version: 3.2.1.1

5.640: Cg: Card state changed to Started

5.640: Cg: Detection timeout timer stopped

5.640: Cg: Polling timer stopped  
5.640: CCgHelper::OwnCgInitialize, CgInitialize: OK.  
5.640: Cg: Sending notification, reason=1  
5.640: CSheetMain::OnCardStateChanged, UWM\_CARD\_STATE\_CHANGED is fired.  
5.640: CSheetMain::OnCardStateChanged, Entered Critical Section  
5.640: CSheetMain::OnCardStateChanged, DebugPortName = \\.\COM3.  
5.640: CSheetMain::OnCardStateChanged, ApplicationPortName = \\.\COM4.  
5.640: CSheetMain::OnCardStateChanged, SmartCardReaderName = .  
5.640: CSheetMain::OnCardStateChanged, DebugPortName = \\.\COM3.  
5.640: CSheetMain::OnCardStateChanged, ApplicationPortName = \\.\COM4.  
5.640: CSheetMain::OnCardStateChanged, SmartCardReaderName = .  
5.640: CSheetMain::OnCardStateChanged, cardDriverCapabilities = 477.  
7.640: CSheetMain::OnCardStateChanged, Left Critical Section  
8.422: CCgHelper::RetrieveCardInfo, Entered CriticalSection!  
8.422: CCgHelper::RetrieveCardInfo, Left CriticalSection!  
8.422: CCgHelper::RetrieveCardInfo, returned: OK.  
8.422: CPagePreparation::Do: Card state: 3.  
8.422: CFlashServices:ExecuteDiagnosticCommand: Executing (D READ 7039 0) command...  
8.422: CPagePreparation::Do, Zaltys detected properly  
15.203: CPagePreparation::Do, product: GlobeSurfer ICON 7.2 E.  
15.203: CPagePreparation::Do, code: MO0201-10959.  
15.203: CPagePreparation::Do: unsupported card (MO0201-10959).  
15.203: Cg: Notification window released  
15.203: Cg: Listener thread stopping  
15.203: Cg: Closing handle for listener thread 0x314  
15.203: Cg: Card information database released  
15.203: CCgHelper::Cleanup, CgShutdown: OK.  
15.203: CCgHelper::Cleanup, CgLeaveExclusiveMode: OK.  
15.203: CPageWizard::ThreadDo, Do: 0xe0ff1001.  
18. 62: CCgHelper::OwnCgUnInitialized, CgUnregisterListener: OK.